



SJN Machinery Co., Ltd.

7SRS5WGMUU+[22-220/1]L[H,P]M THK Miniature Linear Guide Full Ball SRS-G Accuracy and Preload Selectable

Bearing No. 7SRS5WGMUU+[22-220/1]L[H,P]M

7SRS5WGMUU+[22-220/1]L[H,P]M Bearing 2D
drawings and 3D CAD models

Days to Ship	27 Days
Block Type	[Standard] M: Compact
The number of LM blocks combined with a axis	7
Nominal Part Number	5W
Rail Type	Wide Rail
Rail Width W1	10 mm
Mounting Height M	6.5 mm
Rail Length L	22 ~ 220 mm
Radial Clearance	Normal
Accuracy Grade	High Grade / Precision Grade
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	498
Basic Load Rating Static Rating Co(N)	820
Allowable Static Moment MA(N · m)	1.79
Allowable Static Moment MB(N · m)	2.15
Allowable Static Moment MC(N · m)	4.18
Symbols for Dust Resistance	UU: End Seals
Block external dimension W	17 mm
Block external dimension L	22.1 mm



SJN Machinery Co., Ltd.

Number of Block Mounting Holes(holes)	4
Mounting Hole Dimension S(M)	M3
Mounting Hole Screw Depth	Through mm
Block dimension L1	13.7 mm